

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SOLID POWER XL
 Other means of identification : Not applicable
 Recommended use : Machine Warewashing Detergent
 Restrictions on use : Reserved for industrial and professional use.

Product dilution information : 0.06 % - 0.15 %

Company : Ecolab Inc.
 1 Ecolab Place
 St. Paul, Minnesota USA 55102
 1-800-352-5326

Emergency health information : 1-800-328-0026 (US/Canada), 1-651-222-5352 (outside US)

Issuing date : 05/25/2023

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Product AS SOLD

Skin corrosion : Category 1A
 Serious eye damage : Category 1

Product AT USE DILUTION

Not a hazardous substance or mixture.

GHS label elements

Product AS SOLD

Hazard pictograms :



Signal Word : Danger

Hazard Statements : Causes severe skin burns and eye damage.

Precautionary Statements : **Prevention:**

Wash skin thoroughly after handling.

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. Wash contaminated clothing before reuse.

Storage:

Store locked up.

SAFETY DATA SHEET

SOLID POWER XL

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Product AT USE DILUTION

Precautionary Statements

Prevention:

Wash hands thoroughly after handling.

Response:

Get medical advice/ attention if you feel unwell.

Storage:

Store in accordance with local regulations.

Product AS SOLD

Other hazards : None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product AS SOLD

Pure substance/mixture : Mixture

Chemical name

Sodium hydroxide

CAS-No.

1310-73-2

Concentration (%)

60 - 100

Product AT USE DILUTION

No hazardous ingredients

SECTION 4. FIRST AID MEASURES

Product AS SOLD

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Notes to physician : Treat symptomatically.

Most important symptoms and effects, both acute and delayed : See Section 11 for more detailed information on health effects and symptoms.

Product AT USE DILUTION

In case of eye contact : Rinse with plenty of water.

In case of skin contact : Rinse with plenty of water.

SAFETY DATA SHEET

SOLID POWER XL

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Get medical attention if symptoms occur.

SECTION 5. FIRE-FIGHTING MEASURES

Product AS SOLD

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Not flammable or combustible.

Hazardous combustion products : Decomposition products may include the following materials:
Carbon oxides
Sulfur oxides
Oxides of phosphorus

Special protective equipment for fire-fighters : Use personal protective equipment.

Specific extinguishing methods : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Product AS SOLD

Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up : Sweep up and shovel into suitable containers for disposal.

Product AT USE DILUTION

Personal precautions, protective equipment and emergency procedures : Refer to protective measures listed in sections 7 and 8.

Environmental precautions : No special environmental precautions required.

Methods and materials for containment and cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

SECTION 7. HANDLING AND STORAGE

SAFETY DATA SHEET

SOLID POWER XL

Product AS SOLD

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Use only with adequate ventilation. Wash hands thoroughly after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Conditions for safe storage : Do not store near acids. Keep out of reach of children. Store in suitable labeled containers.

Storage temperature : -10 °C to 50 °C

Product AT USE DILUTION

Advice on safe handling : Wash hands after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE). For personal protection see section 8.

Conditions for safe storage : Keep out of reach of children. Store in suitable labeled containers.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Product AS SOLD

Ingredients with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
sodium hydroxide	1310-73-2	C	2 mg/m ³	ACGIH
		C	2 mg/m ³	NIOSH REL
		C	2 mg/m ³	OSHA P0

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.

Hand protection : Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.

Skin protection : Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.

Respiratory protection : Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Product AT USE DILUTION

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

SAFETY DATA SHEET

SOLID POWER XL

Personal protective equipment

Eye protection	: No special protective equipment required.
Hand protection	: No special protective equipment required.
Skin protection	: No special protective equipment required.
Respiratory protection	: No personal respiratory protective equipment normally required.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

	Product AS SOLD	Product AT USE DILUTION
Appearance	: Cast Solid	liquid
Color	: opaque, white	colorless
Odor	: odorless	odorless
pH	: 12.5 - 12.8, (1 %)	10.11 - 10.91
Flash point	: Not applicable	
Odor Threshold	: No data available	
Melting point/freezing point	: No data available	
Initial boiling point and boiling range	: No data available	
Evaporation rate	: No data available	
Flammability (solid, gas)	: Not applicable	
Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Vapor pressure	: No data available	
Relative vapor density	: No data available	
Relative density	: No data available	
Water solubility	: No data available	
Solubility in other solvents	: No data available	
Partition coefficient: n-octanol/water	: No data available	
Autoignition temperature	: No data available	
Thermal decomposition	: No data available	
Viscosity, kinematic	: No data available	
Explosive properties	: No data available	
Oxidizing properties	: No data available	
Molecular weight	: No data available	
VOC	: No data available	

SECTION 10. STABILITY AND REACTIVITY

Product AS SOLD

Reactivity : No dangerous reaction known under conditions of normal use.

SAFETY DATA SHEET

SOLID POWER XL

Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use.
Conditions to avoid	: None known.
Incompatible materials	: Acids Metals Organic materials
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: Carbon oxides Sulfur oxides Oxides of phosphorus

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Eye contact, Skin contact

Potential Health Effects

Product AS SOLD

Eyes	: Causes serious eye damage.
Ingestion	: Causes digestive tract burns.
Inhalation	: May cause nose, throat, and lung irritation.
Chronic Exposure	: Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Eyes	: Health injuries are not known or expected under normal use.
Skin	: Health injuries are not known or expected under normal use.
Ingestion	: Health injuries are not known or expected under normal use.
Inhalation	: Health injuries are not known or expected under normal use.
Chronic Exposure	: Health injuries are not known or expected under normal use.

Experience with human exposure

Product AS SOLD

Eye contact	: Redness, Pain, Corrosion
Skin contact	: Redness, Pain, Corrosion
Ingestion	: Corrosion, Abdominal pain
Inhalation	: Respiratory irritation, Cough

Product AT USE DILUTION

Eye contact	: No symptoms known or expected.
Skin contact	: No symptoms known or expected.

SAFETY DATA SHEET

SOLID POWER XL

Ingestion : No symptoms known or expected.

Inhalation : No symptoms known or expected.

Toxicity

Product AS SOLD Product

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Acute inhalation toxicity : No data available

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Skin corrosion/irritation : No data available

Serious eye damage/eye irritation : No data available

Respiratory or skin sensitization : No data available

Carcinogenicity : No data available

Reproductive effects : No data available

Germ cell mutagenicity : No data available

Teratogenicity : No data available

STOT-single exposure : No data available

STOT-repeated exposure : No data available

Aspiration toxicity : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product AS SOLD

Environmental Effects : Harmful to aquatic life.

Product AT USE DILUTION

Environmental Effects : This product has no known ecotoxicological effects.

Product AS SOLD

Product

Toxicity to fish : 96 h LC50 Pimephales promelas: 137.6 mg/l
Test substance: Product

Toxicity to daphnia and other aquatic invertebrates : 48 h LC50 Ceriodaphnia dubia (water flea): 135.7 mg/l
Test substance: Product

Toxicity to algae : No data available

Persistence and degradability

Product AT USE DILUTION

No data available

Bioaccumulative potential

No data available

Mobility in soil

SAFETY DATA SHEET

SOLID POWER XL

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Product AS SOLD

Disposal methods : Do not contaminate ponds, waterways or ditches with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Product AT USE DILUTION

Disposal methods : Diluted product can be flushed to sanitary sewer.

Disposal considerations : Dispose of in accordance with local, state, and federal regulations.

SECTION 14. TRANSPORT INFORMATION

Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (DOT)

UN number : 1823
Description of the goods : Sodium hydroxide, solid, mixture
Class : 8
Packing group : II
Environmentally hazardous : no

Sea transport (IMDG/IMO)

UN number : 1823
Proper shipping name : SODIUM HYDROXIDE, SOLID, MIXTURE
Class : 8
Packing group : II
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

Product AS SOLD

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Sodium hydroxide	1310-73-2	1000	1656

SAFETY DATA SHEET

SOLID POWER XL

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

California Cleaning Product Right to Know Act of 2017 (SB 258)

This regulation applies to this product.

Hazardous ingredients	CAS-No.	Function	List(s)
Sodium hydroxide	1310-73-2	Cleaning Agent	20
water	7732-18-5	Processing Aid	Not Applicable
Gluconates	527-07-1	Cleaning Agent	Not Applicable
sodium sulfate	7757-82-6	Cleaning Agent	20
Salt of Carboxylic acid derivative	Withheld	Cleaning Agent	Not Applicable
Nonionic surfactant	Withheld	Cleaning Agent	Not Applicable
Alkylene glycol	Withheld	Processing Aid	Not Applicable
sodium aluminate, solid	11138-49-1	Cleaning Agent	10

*refer to ecolab.com/sds for electronic links to designated lists

The ingredients of this product are reported in the following inventories:

Switzerland. New notified substances and declared preparations :
not determined

United States TSCA Inventory :
All substances listed as active on the TSCA inventory

Canadian Domestic Substances List (DSL) :
All components of this product are on the Canadian DSL

Australia. Australian Industrial Chemicals Introduction Scheme (AICIS) :
not determined

New Zealand. Inventory of Chemical Substances :
On the inventory, or in compliance with the inventory

Japan. ENCS - Existing and New Chemical Substances Inventory :
not determined

Korea. Korean Existing Chemicals Inventory (KECI) :
On the inventory, or in compliance with the inventory

Philippines Inventory of Chemicals and Chemical Substances (PICCS) :
On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances in China (IECSC) :

SAFETY DATA SHEET

SOLID POWER XL


not determined

Taiwan Chemical Substance Inventory (TCSI) :
On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Product AS SOLD

NFPA:




HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Product AT USE DILUTION

NFPA:



HMIS III:

HEALTH	0
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Issuing date : 05/25/2023
Version : 1.6
Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.